


Features

- Fast switching
- ESD improved capability
- Low gate charge
- Low reverse transfer capacitances
- JESD22-A114-B ESD rating of class 1C per human body model

HF




Application

- Power switch circuit of adaptor and charger

Mechanical Data

- Case: TO-252
- Molding Compound: UL Flammability Classification Rating 94V-0
- Terminals: Matte tin-plated leads; solderability-per MIL-STD-202, Method 208



TO-252

Ordering Information

Part Number	Package	Shipping Quantity	Marking Code
BL1N60KD	TO-252	80 pcs / Tube & 2500 pcs / Tape & Reel	1N60KD

Maximum Ratings (@ T_C = 25°C unless otherwise specified)

Parameter	Symbol	Value	Unit
Drain-to-Source Voltage	V _{DSS}	600	V
Gate-to-Source Voltage	V _{GSS}	±30	V
Continuous Drain Current (T _C = 25°C)	I _D	1.25	A
Continuous Drain Current (T _C = 100°C)		0.8	A
Pulsed Drain Current (t _p = 10μs, T _C = 25°C)	I _{DM}	5	A
Single Pulse Avalanche Energy *3	E _{AS}	50	mJ
Power Dissipation (T _C = 25°C)	P _D	31	W
Operating Junction Temperature Range	T _J	-55 ~ +150	°C
Storage Temperature Range	T _{STG}	-55 ~ +150	°C

Thermal Characteristics

Parameter	Symbol	Min.	Typ.	Max.	Unit
Thermal Resistance Junction-to-Case	R _{θJC}	-	-	4	°C/W
Thermal Resistance Junction-to-Air *1	R _{θJA}	-	-	40	°C/W

Electrical Characteristics (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)

Symbol	Parameter	Test Condition	Min.	Typ.	Max.	Unit
Static Characteristics						
V _{DSS}	Drain-Source Breakdown Voltage	V _{GS} = 0V, I _D = 250μA	600	-	-	V
I _{DSS}	Zero Gate Voltage Drain Current	V _{DS} = 600V, V _{GS} = 0V	-	-	1	μA
I _{GSS}	Gate-Body Leakage Current	V _{GS} = ±20V, V _{DS} = 0V	-	-	±10	μA
On Characteristics						
R _{DS(ON)}	Drain-Source On-resistance *2	V _{GS} = 10V, I _D = 0.75A	-	-	8	Ω
V _{GS(th)}	Gate Threshold Voltage	V _{DS} = V _{GS} , I _D = 250μA	2	3	4	V
R _G	Gate Resistance	V _{GS} = 0V, f = 1MHz	-	11	-	Ω
Dynamic Characteristics						
C _{ISS}	Input Capacitance	V _{GS} = 0V	-	178	-	pF
C _{OSS}	Output Capacitance	V _{DS} = 25V	-	20	-	
C _{RSS}	Reverse Transfer Capacitance	f = 1.0MHz	-	3	-	
Switching Characteristics						
t _{d(ON)}	Turn-on Delay Time *4	V _{DD} = 300V	-	8	-	ns
t _r	Turn-on Rise Time *4	V _{GS} = 10V	-	30	-	
t _{d(OFF)}	Turn-Off Delay Time *4	R _G = 4.7Ω	-	22	-	
t _f	Turn-Off Fall Time *4	I _D = 1.5A	-	55	-	
Q _G	Total Gate-Charge	V _{DD} = 480V	-	7.7	-	nC
Q _{GS}	Gate to Source Charge	V _{GS} = 10V	-	0.9	-	
Q _{GD}	Gate to Drain (Miller) Charge	I _D = 1.5A	-	5.3	-	
Source-Drain Diode Characteristics						
V _{SD}	Diode Forward Voltage *2	I _{SD} = 1.5A, V _{GS} = 0V	-	-	1.5	V
t _{rr}	Reverse Recovery Time	I _{SD} = 1.5A, V _{GS} = 0V	-	245	-	ns
Q _{rr}	Reverse Recovery Charge	di/dt = 100A/μs	-	795	-	nC

Notes:

- The data tested by surface mounted on a 1 inch² FR-4 board with 2OZ copper
- The data tested by pulsed, pulse width $\leq 300\mu\text{s}$, duty cycle $\leq 2\%$
- The E_{AS} data shows Max. rating. The test condition is $V_{DD} = 100\text{V}$, $V_{GS} = 10\text{V}$, $L = 50\text{mH}$
- Guaranteed by design, not subject to production

Ratings and Characteristics Curves (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)




Fig 1 Power Dissipation




Fig 2 Drain Current




Fig 3 Typical Output Characteristics




Fig 4 On-Resistance vs. Drain Current and Gate Voltage




Fig 5 On-Resistance vs. Gate-Source Voltage




Fig 6 Body-Diode Characteristics




Fig 7 Normalized On-Resistance vs. Junction Temperature




Fig 8 Transfer Characteristics




Fig 9 Capacitance Characteristics




Fig 10 Gate-Charge Characteristics




Fig 11 Normalized Breakdown Voltage vs. Junction Temperature






Fig 12 Normalized $V_{GS(th)}$ vs. Junction Temperature

Package Outline Dimensions (Unit: mm)



Mounting Pad Layout (Unit: mm)



IMPORTANT NOTICE

Changzhou Galaxy Century Microelectronics (GME) reserves the right to make changes without further notice to any product information (copyrighted) herein to make corrections, modifications, improvements, or other changes. GME does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others.