


Features

- ESD / transient protection of high speed data lines
 - IEC 61000-4-2 (ESD): ± 15 kV (air), ± 8 kV (contact)
- Working voltage: $V_{RWM} = 70V$
- Low clamping voltage
- Ultra low leakage
- Ultra low capacitance
- Up to 4 data lines and one power line protects

HF



Typical Applications

- USB 1.1 and 2.0 Data Line Protection
- T1/E1 Secondary IC Protection
- T3/E3 Secondary IC Protection
- HDSL, IDSL Secondary IC Protection
- Video Line Protection
- Microcontroller Input Protection
- Base Stations



Mechanical Data

- Case: SOT-23-6L
- Molding Compound: UL Flammability Classification Rating 94V-0
- Terminals: Matte tin-plated leads; solderability-per MIL-STD-202, Method 208

SOT-23-6L

Ordering Information

Part Number	Package	Shipping Quantity	Marking Code
BL7004S2-6L	SOT-23-6L	3000 pcs / Tape & Reel	7004S

Maximum Ratings (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Value	Unit
IEC 61000-4-2; ESD (Air)	$V_{\text{ESD-A}}$	± 15	kV
IEC 61000-4-2; ESD (Contact)	$V_{\text{ESD-C}}$	± 8	kV
Reverse Voltage	V_R	70	V
Repetitive Peak Reverse Voltage	V_{RRM}	70	V
Forward Current	I_F	200	mA
Repetitive Peak Forward Current	I_{FRM}	450	mA
Non-Repetitive Peak Forward Current $t = 1.0 \text{ ms}$	I_{FSM}	1	A

Thermal Characteristics

Parameter	Symbol	Value	Unit
Thermal Resistance Junction-to-Air	$R_{\theta\text{JA}}$	556	$^\circ\text{C/W}$
Junction Temperature	T_J	$-40 \sim +125$	$^\circ\text{C}$
Storage Temperature Range	T_{STG}	$-55 \sim +150$	$^\circ\text{C}$

Electrical Characteristics (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Reverse Stand-off Voltage	V_{RWM}		-	-	70	V
Reverse Breakdown Voltage	$V_{(\text{BR})}$	$I_T = 1\text{mA}$	85	-	-	V
Reverse Leakage Current	I_R	$V_{\text{RWM}} = 70\text{V}$	-	-	0.2	μA
Forward Voltage	V_F	$I_F = 10\text{mA}$	-	-	1.2	V
Junction Capacitance	C_J	$V_R = 0\text{V}$, $f = 1\text{MHz}$, between I/O	-	1.5	3	pF
		$V_R = 0\text{V}$, $f = 1\text{MHz}$ any I/O to V_N	-	2.9	5	pF

Ratings and Characteristic Curves (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)




Fig. 1 Typical Reverse Characteristic




Fig. 2 Typical Forward Characteristic





Fig. 3 Junction Capacitance vs. Reverse Voltage


Package Outline Dimensions (Unit: mm)



SOT-23-6L		
Dimension	Min.	Max.
A	2.80	3.00
B	1.50	1.70
C	1.00	1.20
D	0.35	0.45
E	0.35	0.55
G	0.90	1.00
H	0.02	0.10
J	0.10	0.20
K	2.60	3.00

Package Outline Dimensions (Unit: mm)

SOT-23-6L



IMPORTANT NOTICE

Changzhou Galaxy Century Microelectronics (GME) reserves the right to make changes without further notice to any product information (copyrighted) herein to make corrections, modifications, improvements, or other changes. GME does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others.